Unique log grapple with tilt function

– Developed to make logging more efficient.
The T220 tilt grapple is a normal loading grapple with built-in tilt function, but still works with the same hydraulics as a traditional loading grapple. You only need 2 hydraulic lines (grapple open/close).
The tilt function is controlled wirelessly. Two extra control buttons/pedals (tilt up/tilt down) are included in the delivery. These control buttons can be installed in a suitable place. 2 batteries and a battery charger are also included in the delivery.

FEATURES
Fast and easy to use – increases productivity
Stable both in felling and loading position
Easy to install
No additional hydraulic lines are needed – only grapple open and grapple close
Completely stepless control – for example, stop the tilt half way if necessary
Control system alternatives
Standard: 1 double-acting hydraulic line, grapple open/close + Remote control for tilt function
Grapple claw alternatives
Standard: Traditional log grapple claws (closed ends)
Option: Energy grapple claws (open ended)
Option: A-model claws (with diagonal plates)

Technical information

Model	T220 *G2*
Grapple size	0,22 m2
Weight	155 kg
Rec. working pressure	200-230 bar
Rec. oil flow rate	30 – 50 l/min.
Opening of grapple	1200 mm
Attachment standard	173/6

© Mecanil Oy Ab 2018. All rights reserved.