

Unique log grapple with tilt function

- Developed to make logging more efficient.
 The T220 tilt grapple is a normal loading grapple with built-in tilt function, but still works with the same hydraulics as a traditional loading grapple. You only need 2 hydraulic lines (grapple open/close).
 The tilt function is controlled wirelessly. Two extra control buttons/pedals (tilt up/tilt down) are included in the delivery. These control buttons can be installed in a suitable place. 2 batteries and a battery charger are also included in the delivery.



FEATURES

- Fast and easy to use - increases productivity
- Stable both in felling and loading position
- Easy to install
- No additional hydraulic lines are needed - only grapple open and grapple close
- Completely stepless control - for example, stop the tilt half way if necessary
- Control system alternatives**
- Standard: 1 double-acting hydraulic line, grapple open/close + Remote control for tilt function
- Grapple claw alternatives**
- Standard: Traditional log grapple claws (closed ends)
- Option: Energy grapple claws (open ended)
- Option: A-model claws (with diagonal plates)

Technical information

Model	T220 <i>G2</i>
Grapple size	0,22 m2
Weight	155 kg
Rec. working pressure	200-230 bar
Rec. oil flow rate	30 - 50 l/min.
Opening of grapple	1200 mm
Attachment standard	173/6